

## **DECLARATION OF PERFORMANCE No. DoP-1-215PK2**

**1. Unique identification code of the product-type:**

**MD215PK2**

**2. Intended uses:**

underlays for discontinuous roofing, underlays for walls

**3. Manufacturer:**

Info-GLOBAL sp. j.  
ul. Długa 67  
63-400 Ostrów Wielkopolski  
PL

**Production plant:**

ul. Osiedle Przemysłowe 22  
69-100 Słubice  
PL

**4. System of AVCP:**

System 3

**5. Harmonized standard:**

EN 13859-1:2010  
EN 13859-2:2010

**Notified body:**

No. 1434 - Polskie Centrum Badań i Certyfikacji S.A.

## 6. Declared performances:

Essential characteristics		Performance	Unit of measure	Harmonised technical specification
Reaction to fire		Class E	-	EN 13859-1:2010 EN 13859-2:2010
Water tightness		Class W1	-	
Tensile mechanical properties	Tensile strength along	320 (+60;-60)	N/50mm	
	Tensile strength across	180 (+50;-50)	N/50mm	
	Elongation along	80 (+40;-40)	%	
	Elongation across	150 (+70;-70)	%	
Resistance to tearing along		250 (+60;-60)	N	
Resistance to tearing across		250 (+60;-60)	N	
Flexibility at low temperature		-30	°C	
Water tightness after artificial aging		Class W1	-	
Tensile mechanical properties after artificial aging	Tensile strength along	250 (+50;-50)	N/50mm	
	Tensile strength across	140 (+40;-40)	N/50mm	
	Elongation along	70 (+30;-30)	%	
	Elongation across	110 (+60;-60)	%	
Water vapour transmission ( $S_d$ )		0,04 (+0,02;-0,02)	m	EN 13859-2:2010

***The performances of the product identified above are in conformity with the set of declared performances. This declaration of performance is issued according to the regulation (EU) no. 305/2011 under the sole responsibility of the manufacturer indicated above.***

**Signed on behalf of the manufacturer by:**

mgr inż. Kinga Frąszczak – Quality Control Manager

KIEROWNIK DZIAŁU  
KONTROLI JAKOŚCI  
mgr inż. Kinga Frąszczak

Ostrów Wielkopolski, 17.06.2024